



## Synqron 5W-30 | Fully synthetic engine oil

### Property

- proven fuel saving and reduced emissions thanks to lowered HTHS viscosity
- excellent cold starting characteristics
- good high temperature properties
- protects against premature ignition at low speed (LSPI → Low Speed Pre-Ignition)

### Application area

- only suitable for petrol engines
- especially suitable for GM and Opel
- suitable for catalytic converters
- suitable for passenger cars and light commercial vehicles

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Property	Unit	Value
Viscosity SAE	-	5W-30
Color	-	brown
Viscosity @ 40°C	cSt	55
Viscosity @ 100°C	cSt	9.9
Viscosity index	-	168
Density @ 15°C	kg/l	0.847
Viscosity HTHS @ 150°C	mPa·s	2.9
Zinc content	ppm	850
Pour Point	°C	-39
Flash Point	°C	221

### Available packaging

1 L bottle	Case 12 x 1 L bottles
50 kg drum (approx. 59 L)	175 kg drum (approx. 207 L)

### Specifications

API Resource Conserving, SL*, SM*, SN*, SN Plus*, SP
Chrysler MS 6395, 13340
Fiat 9.55535-CR1
Ford M2C929-A, M2C946-A, M2C946-B1, M2C961-A1
GM 4718M, 6094M, dexos1*, dexos1 Gen 2, LL-A-025*
ILSAC GF-5*, GF-6A
Opel OV 040 1547 - G30
VW VWC 53034

\* Additional Specifications