



Avanza 5W-30 | Fully synthetic engine oil

Property

- proven fuel saving and reduced emissions thanks to lowered HTHS viscosity
- excellent cold starting characteristics
- good high temperature properties
- protects against premature ignition at low speed (LSPI → Low Speed Pre-Ignition)

Application area

- especially suitable for Ford
- suitable for passenger cars and light commercial vehicles

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Property	Unit	Value
Viscosity SAE	-	5W-30
Color	-	brown
Viscosity @ 40°C	cSt	54
Viscosity @ 100°C	cSt	9.8
Viscosity index	-	169
Density @ 15°C	kg/l	0.851
Viscosity CCS @ -30°C	mPa.s	4010
Viscosity HTHS @ 150°C	mPa.s	2.9
Zinc content	ppm	1050
Sulphated ash	g/100g	1.11
Total base number	mg KOH/g	10.2
Pour Point	°C	-39
Flash Point	°C	230

Available packaging

1 L bottle	4 L canister
Case 12 x 1 L bottles	Case 6 x 4 L canisters
50 kg drum (approx. 59 L)	175 kg drum (approx. 206 L)

Specifications

ACEA A1/B1*, A5/B5
API SL*, SM*, SN*, SN Plus*, SP
Ford M2C913-A*, M2C913-B*, M2C913-C*, M2C913-D
Jaguar Land Rover STJLR.03.5003
Renault RN0700
VW VWC 53036

* Additional Specifications