



Avanza 10W-40 | Synthetic blend engine oil

Property

- reduced emissions
- keeps the engine clean and protects against wear and corrosion
- good cold starting characteristics
- good high temperature properties

Application area

- suitable for modern classics
- suitable for passenger cars and light commercial vehicles

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	10W-40
Color	-	brown
Viscosity @ 40°C	cSt	95.5
Viscosity @ 100°C	cSt	14.4
Viscosity index	-	156
Density @ 15°C	kg/l	0.86
Viscosity CCS @ -25°C	mPa.s	4210
Zinc content	ppm	1050
Pour Point	°C	-34
Flash Point	°C	210

Available packaging

1 L bottle	4 L canister
Case 12 x 1 L bottles	Case 6 x 4 L canisters
54 kg drum (approx. 63 L)	180 kg drum (approx. 209 L)

Specifications

ACEA A2/B2*, A3/B3*, A3/B4
API SL*, SM*, SN*, SN Plus*, SP
Fiat 9.55535-D2, G2
MB 229.1*, 229.3
PSA B71 2294, B71 2300
Renault RN0700, RN0710
VW 500 00*, 501 01*, 502 00, 505 00

* Additional Specifications