



## Performance 20W-50 | Mineral Engine oil

### Property

- best resistance to oxidation (ageing stability)
- compatible with all seal materials (old and new)
- keeps the engine clean and protects against wear and corrosion
- excellent high temperature properties
- protects against premature ignition at low speed (LSPI → Low Speed Pre-Ignition)

### Application area

- guaranteed lubrication reliability, including for motor sport use
- suitable for classic cars
- suitable for catalytic converters
- can be used in motor sport
- suitable for cars

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Property	Unit	Value
Viscosity SAE	-	20W-50
Color	-	brown
Viscosity @ 40°C	cSt	151
Viscosity @ 100°C	cSt	18
Viscosity index	-	132
Density @ 15°C	kg/l	0.87
Viscosity CCS @ -15°C	mPa.s	7330
Zinc content	ppm	1050
Pour Point	°C	-25
Flash Point	°C	218

### Available packaging

1 L bottle	Case 12 x 1 L bottles
54 kg drum (approx. 62 L)	180 kg drum (approx. 207 L)

### Specifications

ACEA A2/B2*, A3/B3*, A3/B4
API SL*, SM*, SN*, SN Plus*, SP
MB 229.1
VW 500 00*, 501 01, 505 00

\* Additional Specifications