



Motorcycle 10W-50 | Fully synthetic 4-cycle engine oil

Property

- effortless gear shifting in all temperature ranges and under load
- compatible with all seal materials (old and new)
- good cold starting characteristics
- excellent high temperature properties
- prevents clutch slipping

Application area

- suitable for wet clutch
- can be used in motor sport
- can be used for primary drive
- suitable for motorcycles with 4-stroke engines

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	10W-50
Color	-	brown
Viscosity @ 40°C	cSt	125.66
Viscosity @ 100°C	cSt	17.77
Viscosity index	-	157
Density @ 15°C	kg/l	0.848
Viscosity @ -25°C	mPa·s	4840
Viscosity HTHS @ 150°C	mPa·s	4.27
NOACK [%]	-	7
Zinc content	ppm	920
Pour Point	°C	-36
Flash Point	°C	244

Available packaging

1 L bottle	Case 12 x 1 L bottles
50 kg drum (approx. 59 L)	175 kg drum (approx. 206 L)

Specifications

API SL*, SM*, SN
JASO MA*, MA2

* Additional Specifications