



Synqron 0W-40 | Fully synthetic engine oil

Property

- best resistance to oxidation (ageing stability)
- keeps the engine clean and protects against wear and corrosion
- excellent cold starting characteristics
- good cold starting characteristics
- very good high temperature properties

Application area

- suitable for Porsche and Mercedes-Benz
- suitable for cars

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	0W-40
Color	-	brown
Viscosity @ 40°C	cSt	71.2
Viscosity @ 100°C	cSt	13
Viscosity index	-	186
Density @ 15°C	kg/l	0.845
Viscosity @ -35°C	mPa.s	5400
Viscosity HTHS @ 150°C	mPa.s	3.7
Zinc content	ppm	1050
Pour Point	°C	-48
Flash Point	°C	230

Available packaging

1 L bottle	Case 12 x 1 L bottles
175 kg drum (approx. 206 L)	

Specifications

ACEA A2/B2*, A3/B3*, A3/B4
API SJ*, SL*, SL/CF*, SM*, SN/CF
BMW Longlife-01
Fiat 9.55535-H2, M2, N2, Z2
Ford M2C937-A
MB 226.5*, 229.1*, 229.3*
MB-Approval 229.5
Porsche A40
PSA B71 2296
Renault RN0700, RN0710
VW 500 00*, 501 01*, 502 00, 505 00

* Additional Specifications