

Axxept 5W-30 | Fully synthetic engine oil

Property

- best resistance to oxidation (ageing stability)
- keeps the engine clean and protects against wear and corrosion
- excellent cold starting characteristics
- very good high temperature properties
- proven fuel saving and reduced emissions
- Low SAPS technology with reduced content of sulphated ash, phosphorus and sulphur
- increases the service life of exhaust aftertreatment systems such as catalytic converters (SCR) and particulate filters (GPF/DPF) in gasoline and diesel engines

Application area

- can be used where an ACEA A3/B3-08 or A3/B4-08 is required
- especially suitable for GM and Opel
- suitable for cars
- suitable for gasoline and diesel engines

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties		
Eigenschaft	Einheit	Wert
Viscosity SAE	-	5W-30
Color	-	brown
Viscosity @ 40°C	cSt	70.3
Viscosity @ 100°C	cSt	12.2
Viscosity index	-	173
Density @ 15°C	kg/l	0.852
Viscosity @ -30°C	mPa·s	5300
Viscosity HTHS @ 150°C	mPa·s	3.6
Zinc content	ppm	880
Pour Point	°C	-36
Flash Point	°C	230

Available packaging	
1 L bottle	Case 12 x 1 L bottles
175 kg drum (approx. 205 L)	

Specifications
ACEA C2, C3
API SJ*, SL*, SL/CF*, SM*, SN/CF
BMW Longlife-01*, 04
Chrysler MS 6395, 11106
Fiat 9.55535-G1, S1, S3
Ford M2C917-A
GM dexos 2, LL-A-025*, LL-B-025*
MB 229.31*, 229.51
PSA B71 2290
Renault RN0700
VW 500 00*, 501 01*, 502 00, 505 00, 505 01
· · · · · · · · · · · · · · · · · · ·

^{*} Additional Specifications

Product number: 21721