



Marine FC-W 10W-30 | Engine oil for outboard 4-cycle engines

Property

- best resistance to oxidation (ageing stability)
- keeps the engine clean and protects against wear and corrosion
- exceeds the strict requirements of the NMMA (National Marine Manufacturers Association) FC-W and FC-W Catalyst Compatible standards

Application area

- suitable for freshwater and saltwater boat engines
- suitable for catalytic converters
- suitable for use in different makes of 4-stroke outboard engines such as Bombardier, Evinrude, Honda, Johnson, Mercury Marine, Sea-Doo, Suzuki, Yamaha and others

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	10W-30
Color	-	brown
Viscosity @ 40°C	cSt	72
Viscosity @ 100°C	cSt	11.5
Viscosity index	-	153
Density @ 15°C	kg/l	0.87
Pour Point	°C	-33
Flash Point	°C	226

Available packaging

1 L bottle	Case 12 x 1 L bottles
180 kg drum (approx. 207 L)	

Specifications

API SL*, SM
NMMA FC-W, FC-W Catalyst Compatible

* Additional Specifications