



## Avanza 0W-30 | Fully synthetic engine oil

### Property

- best resistance to oxidation (ageing stability)
- proven fuel saving and reduced emissions thanks to lowered HTHS viscosity
- excellent cold starting characteristics
- good high temperature properties

### Application area

- especially suitable for Volvo
- suitable for cars

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	0W-30
Color	-	brown
Viscosity @ 40°C	cSt	53.1
Viscosity @ 100°C	cSt	10.1
Viscosity index	-	181
Density @ 15°C	kg/l	0.842
Viscosity @ -35°C	mPa.s	6000
Viscosity HTHS @ 150°C	mPa.s	3.1
Zinc content	ppm	1050
Sulphated ash	g/100g	1
Total base number	mg KOH/g	10.2
Pour Point	°C	-42
Flash Point	°C	220

### Available packaging

175 kg drum (approx. 208 L)	
-----------------------------	--

### Specifications

ACEA A1/B1*, A5/B5
API SL
Renault RN0700
Volvo VCC 95200377

\* Additional Specifications