



## Unitrac STOU 10W-30 | Multi-purpose tractor oil (STOU)

### Property

- best resistance to oxidation (ageing stability)
- good cold starting characteristics
- good high temperature properties
- excellent detergent and dispersant properties (cleans and dirt cannot form deposits)

### Application area

- universally suitable for engines, transmissions, hydraulic systems, wet brakes and final drives

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.
- May also be used as hydraulic fluid if a HLP 46, HLP 68, HVLP 68 or HVLP-D is specified.

### Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	10W-30 / 80W
Viscosity ISO	-	68
Color	-	brown
Viscosity @ 40°C	cSt	70.3
Viscosity @ 100°C	cSt	10.9
Viscosity index	-	145
Density @ 15°C	kg/l	0.87
Pour Point	°C	-30
Flash Point	°C	214

### Available packaging

54 kg drum (approx. 62 L)	180 kg drum (approx. 207 L)
---------------------------	-----------------------------

### Specifications

ACEA E2
Allison C-3*, C-4
API CF*, CF-4, GL-4, SF
Caterpillar TO-2
Ford M2C159-C
John Deere JDM J27
Massey Ferguson CMS M1135, M1139, M1144, M1145
ZF TE-ML 06B, 06C, 06D, 06F, 06Q, 06R, 07B

\* Additional Specifications