



Unitrac STOU 10W-40 | Multi-purpose tractor oil (STOU)

Property

- best resistance to oxidation (ageing stability)
- good cold starting characteristics
- very good high temperature properties
- excellent detergent and dispersant properties (cleans and dirt cannot form deposits)

Application area

- universally suitable for engines, transmissions, hydraulic systems, wet brakes and final drives

Note

- May also be used as hydraulic fluid if a HLP 46, HLP 68, HVLP 68 or HVLP-D is specified.
- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

| Eigenschaft | Einheit | Wert |
|-------------------|---------|-----------------|
| Viscosity SAE | - | 10W-40 / 80W-90 |
| Color | - | brown |
| Viscosity @ 40°C | cSt | 91.36 |
| Viscosity @ 100°C | cSt | 14.44 |
| Viscosity index | - | 164 |
| Density @ 15°C | kg/l | 0.861 |
| Pour Point | °C | -33 |
| Flash Point | °C | 221 |

Available packaging

| | |
|---------------------------|-----------------------------|
| 54 kg drum (approx. 63 L) | 180 kg drum (approx. 209 L) |
|---------------------------|-----------------------------|

Specifications

| |
|--|
| ACEA E2 |
| Allison C-3*, C-4 |
| API CF*, CF-4*, CG-4, GL-4 |
| Caterpillar TO-2 |
| Ford M2C159-C |
| John Deere JDM J27 |
| Massey Ferguson CMS M1135, M1139, M1144, M1145 |
| ZF TE-ML 06B, 06C, 06D, 06F, 06Q, 06R, 07B |

* Additional Specifications