



Syngron 75W-90 | Fully synthetic gear lubricant

Property

- extreme pressure absorption capacity
- outstanding seal compatibility
- very high resistance to wear, corrosion and foaming
- excellent low temperature behaviour
- constant viscosity and excellent oxidation stability (ageing stability)

Application area

- can be used where a GL-3 is demanded
- universal application for transmissions and axles of motor vehicles
- for moderately or highly stressed axles with normal or hypoid gears

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	75W-90
Color	-	brown
Viscosity @ 40°C	cSt	91
Viscosity @ 100°C	cSt	15
Viscosity index	-	175
Density @ 15°C	kg/l	0.876
Viscosity @ -40°C	mPa·s	150000
Pour Point	°C	-42
Flash Point	°C	160

Available packaging

1 L bottle	Case 12 x 1 L bottles
25 L pail	54 kg drum (approx. 62 L)
180 kg drum (approx. 205 L)	

Specifications

API GL-4, GL-5
Fiat 9.55550-DA3, DA4, DA12, MX3, MX4
MIL-L-2105, L-2105D