



## High Performance 80W-90 | Limited-slip differential oil

### Property

- extreme pressure absorption capacity
- outstanding seal compatibility
- very high resistance to wear, corrosion and foaming
- excellent low temperature behaviour
- constant viscosity and excellent oxidation stability (ageing stability)

### Application area

- suitable for passenger cars, commercial vehicles and construction machinery
- suitable for drive axles and limited-slip differentials
- for moderately or highly stressed axles with normal or hypoid gears

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	80W-90
Color	-	brown
Viscosity @ 40°C	cSt	138
Viscosity @ 100°C	cSt	14.3
Viscosity index	-	101
Density @ 15°C	kg/l	0.887
Viscosity @ -26°C	mPa·s	150000
Pour Point	°C	-27
Flash Point	°C	200

### Specifications

API GL-5
Fiat 9.55550-DA13, DA14
ZF TE-ML 05C, 12C, 16E, 21C

### Available packaging

1 L bottle	Case 12 x 1 L bottles
25 L pail	54 kg drum (approx. 61 L)
180 kg drum (approx. 203 L)	