



ATF M3 Plus | Automatic transmission fluid

Property

- outstanding seal compatibility
- very high resistance to wear, corrosion and foaming
- smooth gear changing at all temperatures and under load

Application area

- suitable for passenger cars, commercial vehicles, construction machinery and ships
- for automatic transmissions with and without torque converter
- suitable for use in power steering systems, gearboxes or hydraulic systems if a ATF is recommended
- miscible with all ATF DEXRON II / DEXRON / MERCON
- can be used where an ESSO LT 71141, Shell LA2634, Texaco 7045-E, Texaco ETL-8072 B or Texaco N402 is recommended
- not recommended for continuously variable transmissions (CVT)

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Property	Unit	Value
Color	-	red
Viscosity @ 40°C	cSt	36.46
Viscosity @ 100°C	cSt	7.4
Viscosity index	-	175
Density @ 15°C	kg/l	0.86
Viscosity Brookfield @ -40°C	mPa·s	16300
Pour Point	°C	-43
Flash Point	°C	200

Available packaging

1 L bottle	Case 12 x 1 L bottles
25 L pail	50 kg drum (approx. 58 L)
175 kg drum (approx. 203 L)	

Specifications

Allison C-3*, C-4, TES-295
Caterpillar TO-2
Chrysler MS 7176 (ATF +3)
DTRF 13C110, 13C140, 13C170, 13C180, 38B100
Ford Mercon
GM DEXRON III H
MAN 339 Typ V1, Z1, Z11
MB 236.3, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11
MM SP-II
Voith 55.6335.3x (G607)
ZF TE-ML 03D, 04D, 14A, 14B, 17C, 20B

* Additional Specifications