



THF | Universal Tractor Transmission Oil (UTTO)

Property

- outstanding seal compatibility
- very high resistance to wear, corrosion and foaming
- constant viscosity and excellent oxidation stability (ageing stability)
- controlled and reduced chatter on wet brake systems
- excellent detergent and dispersant properties (cleans and dirt cannot form deposits)

Application area

- universally suitable for hydraulic systems, transmissions and wet brakes

Note

- May also be used as hydraulic fluid if a HLP 46, HLP 68, HVLP 68 or HVLP-D is specified.
- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Property	Unit	Value
Viscosity SAE	-	80W
Color	-	brown
Viscosity @ 40°C	cSt	67.5
Viscosity @ 100°C	cSt	11
Viscosity index	-	154
Density @ 15°C	kg/l	0.87
Pour Point	°C	-36
Flash Point	°C	220

Available packaging

25 L pail	54 kg drum (approx. 62 L)
180 kg drum (approx. 206 L)	

Specifications

AGCO Powerfluid 821XL
Allison C-3, C-4
API GL-4
Case MS 1206 (Hy-Tran/IH-B6), 1207 (Hy-Tran Plus), 1209 (Hy-Tran Ultra)
Case New Holland CNH MAT 3505, 3506, 3509, 3525
Caterpillar TO-2
Deutz Allis
Fendt
Fiat
Ford M2C86-B, M2C86-C
Ford New Holland FNHA-2-C-200.00, FNHA-2-C-201.00
John Deere JDM J20C, J20D
Landini
Massey Ferguson CMS M1135, M1141, M1143, M1145
New Holland NH-410B, NH-420A
Renault
Same
Volvo VCE