



## TO-4 SAE 10W | Transmission Drive Train Oil (TDTO)

### Property

- flawless transmission protection, even under excessive loads and vibration
- outstanding seal compatibility
- no wet brake chatter
- greater transmission performance through optimised friction values
- TDTO (Transmission Drive Train Oil) tested in cooperation with Caterpillar

### Application area

- can be used where a Caterpillar HYDO Advanced is recommended
- especially suitable for power shift transmissions, axles and lateral drive systems of construction machinery

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Eigenschaft	Einheit	Wert
Viscosity SAE	-	10W
Color	-	brown
Viscosity @ 40°C	cSt	39
Viscosity @ 100°C	cSt	6.5
Viscosity index	-	119
Density @ 15°C	kg/l	0.86
Pour Point	°C	-33
Flash Point	°C	220

### Available packaging

180 kg drum (approx. 209 L)	
-----------------------------	--

### Specifications

Allison C-3*, C-4
API CF, GL-4
Caterpillar TO-2*, TO-4
Dana Powershift
Eaton Vickers 35VQ25
Komatsu KES 07.868.1
ZF TE-ML 03C

\* Additional Specifications