



ATF XD-Z | Fully synthetic automatic transmission fluid

Property

- outstanding seal compatibility
- very high resistance to wear, corrosion and foaming
- excellent low temperature behaviour
- constant viscosity and excellent oxidation stability (ageing stability)
- smooth gear changing at all temperatures and under load

Application area

- especially suitable for all ZF Ecomat and EcoLife transmissions where an EcoFluid A Life, A Plus or Life is recommended
- specially developed for heavy-duty commercial vehicles and buses
- appropriate for change intervals of up to 150,000 km / 3 years

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Property	Unit	Value
Color	-	light yellow
Viscosity @ 40°C	cSt	61.8
Viscosity @ 100°C	cSt	10.2
Viscosity index	-	153
Density @ 15°C	kg/l	0.843
Pour Point	°C	-51
Flash Point	°C	240

Available packaging

25 L pail	50 kg drum (approx. 59 L)
175 kg drum (approx. 208 L)	

Specifications

IVECO 18-1807 AG3/II
MAN 339 Typ Z4, Z13
ZF TE-ML 04D, 14E, 16N, 16Q, 20F, 25F