



## Cryptogear 75W-90 | Fully synthetic gear lubricant

### Property

- outstanding seal compatibility
- very high resistance to wear, corrosion and foaming
- excellent low temperature behaviour
- constant viscosity and excellent oxidation stability (ageing stability)
- effortless gear shifting in all temperature ranges and under load

### Application area

- can be used where a GL-3 is demanded
- appropriate for change intervals of up to 450,000 km / 3 years (Longlife) and thus lower maintenance costs
- especially suitable for high-performance transmissions
- especially suitable for highly loaded automated I-Shift transmissions in Volvo and Renault Trucks
- suitable for manual gearboxes
- specially developed for heavy-duty commercial vehicles and buses

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Property	Unit	Value
Viscosity SAE	-	75W-90
Color	-	brown
Viscosity @ 100°C	cSt	17.9
Density @ 15°C	kg/l	0.86
Pour Point	°C	-48
Flash Point	°C	196

### Available packaging

50 kg drum (approx. 58 L)	175 kg drum (approx. 203 L)
---------------------------	-----------------------------

### Specifications

API GL-4
Renault
Volvo 97305*, 97307*, 97315

\* Additional Specifications