



## Valesta ISO 46 | Universal industrial lubricant

### Property

- very high resistance to wear, corrosion and foaming
- constant viscosity and excellent oxidation stability (ageing stability)
- increased load-carrying capability → Reduced wear

### Application area

- suitable for turbines, compressors, vacuum pumps, hydraulic systems and gearboxes in industrial machinery
- universal applications

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

| Eigenschaft       | Einheit | Wert         |
|-------------------|---------|--------------|
| Viscosity ISO     | -       | 46           |
| Color             | -       | light yellow |
| Viscosity @ 40°C  | cSt     | 46           |
| Viscosity @ 100°C | cSt     | 7            |
| Viscosity index   | -       | 109          |
| Density @ 15°C    | kg/l    | 0.879        |
| Pour Point        | °C      | -29          |
| Flash Point       | °C      | 210          |

### Available packaging

|                           |                             |
|---------------------------|-----------------------------|
| 4 L canister              | 25 L canister               |
| 54 kg drum (approx. 61 L) | 180 kg drum (approx. 205 L) |

### Specifications

|                         |
|-------------------------|
| DIN 51506 VBL, VCL, VDL |
| DIN 51517-3 CLP         |
| DIN 51524-2 HLP         |