



Valesta ISO 150 | Universal industrial lubricant

Property

- very high resistance to wear, corrosion and foaming
- constant viscosity and excellent oxidation stability (ageing stability)
- increased load-carrying capability → Reduced wear

Application area

- suitable for turbines, compressors, vacuum pumps, hydraulic systems and gearboxes in industrial machinery
- universal applications

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Viscosity ISO	-	150
Color	-	brown
Viscosity @ 40°C	cSt	150
Viscosity @ 100°C	cSt	15
Viscosity index	-	100
Density @ 15°C	kg/l	0.894
Pour Point	°C	-25
Flash Point	°C	230

Available packaging

4 L canister	25 L canister
54 kg drum (approx. 60 L)	180 kg drum (approx. 201 L)

Specifications

DIN 51506 VBL, VCL, VDL
DIN 51517-3 CLP
DIN 51524-2 HLP