



## Valesta ISO 220 | Universal industrial lubricant

### Property

- very high resistance to wear, corrosion and foaming
- constant viscosity and excellent oxidation stability (ageing stability)
- increased load-carrying capability → Reduced wear

### Application area

- suitable for turbines, compressors, vacuum pumps, hydraulic systems and gearboxes in industrial machinery
- universal applications

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

| Eigenschaft       | Einheit | Wert  |
|-------------------|---------|-------|
| Viscosity ISO     | -       | 220   |
| Color             | -       | brown |
| Viscosity @ 40°C  | cSt     | 220   |
| Viscosity @ 100°C | cSt     | 19    |
| Viscosity index   | -       | 97    |
| Density @ 15°C    | kg/l    | 0.899 |
| Pour Point        | °C      | -15   |
| Flash Point       | °C      | 240   |

### Specifications

|                 |
|-----------------|
| DIN 51506 VBL   |
| DIN 51517-3 CLP |

### Available packaging

|                           |                             |
|---------------------------|-----------------------------|
| 4 L canister              | 25 L canister               |
| 54 kg drum (approx. 60 L) | 180 kg drum (approx. 200 L) |