



Valesta ISO 320 | Universal industrial lubricant

Property

- very high resistance to wear, corrosion and foaming
- constant viscosity and excellent oxidation stability (ageing stability)
- increased load-carrying capability → Reduced wear

Application area

- suitable for turbines, compressors, vacuum pumps, hydraulic systems and gearboxes in industrial machinery
- universal applications

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Viscosity ISO	-	320
Color	-	brown
Viscosity @ 40°C	cSt	320
Viscosity @ 100°C	cSt	28
Viscosity index	-	100
Density @ 15°C	kg/l	0.901
Pour Point	°C	-12
Flash Point	°C	250

Specifications

DIN 51506 VBL
DIN 51517-3 CLP

Available packaging

4 L canister	25 L canister
54 kg drum (approx. 60 L)	180 kg drum (approx. 200 L)