



## Valesta ISO 680 | Universal industrial lubricant

### Property

- very high resistance to wear, corrosion and foaming
- constant viscosity and excellent oxidation stability (ageing stability)
- increased load-carrying capability → Reduced wear

### Application area

- suitable for turbines, compressors, vacuum pumps, hydraulic systems and gearboxes in industrial machinery
- universal applications

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Eigenschaft	Einheit	Wert
Viscosity ISO	-	680
Color	-	brown
Viscosity @ 40°C	cSt	680
Density @ 15°C	kg/l	0.92
Pour Point	°C	-3
Flash Point	°C	320

### Specifications

DIN 51517-3 CLP

### Available packaging

4 L canister	25 L canister
54 kg drum (approx. 59 L)	180 kg drum (approx. 196 L)