



Prestolite | Multi-purpose cleaner

Property

- undiluted multi-purpose cleaner
- effortlessly removes oil, grease and dirt
- non-corrosive
- sensitive to frost

Application area

- for cleaning the engine block and chassis of cars, trucks, construction machinery, machines and vehicle bodies
- for cleaning inside vehicles of every type
- for cleaning floors in garages or businesses as well as tarpaulins or similar
- suitable for all types of cleaning (e.g. manual and spray method, steam, high-pressure and ultrasonic cleaning)
- not suitable for systems with coalescence filter
- can be used with emulsion splitting plants

Dosage for cleaning with a steam or high-pressure jet cleaner

- Heavy soiling → Mixing ratio 1:3
- Medium soiling → Mixing ratio 1:4
- Normal soiling → Mixing ratio 1:5
- Application: Start mixing in the reservoir of the device.

Dosage for engine and chassis cleaning

- Heavy soiling → Mixing ratio 1:1 (allow to react for 5-10 min)
- Medium soiling → Mixing ratio 1:3 (allow to react for 5 min)
- Normal soiling → Mixing ratio 1:4 to 1:5
- Application: Rinse after exposure with a pressurised water jet or a high-pressure or steam jet cleaner.

Dosage for general cleaning

- Mixing ratio 1:1 to 1:100 as required
- Application: Can be used in cold or hot water. Allow to react for 2-3 minutes for heavy soiling.

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Available packaging

25 L canister	200 L drum
---------------	------------