



Brake Fluid DOT 4 | Brake fluid

Property

- excellent thermal stability
- ensures swelling of natural, styrene-butadiene and EPDM rubbers according to specifications
- excellent corrosion protection for metal parts, even if the brake fluid is mixed with water
- optimum braking performance, even at low sub-zero temperatures
- miscible with other brake fluids with DOT 3 or DOT 4 specifications
- prevents vapour lock thanks to high dry and wet boiling point

Application area

- ideally suitable for hydraulic brake and clutch systems

Note

- Attacks paint/varnish. Even an effective brake fluid can absorb water during continual use.
- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Color	-	yellow
Viscosity @ 100°C	cSt	1.5
Density @ 15°C	kg/l	1.05
Viscosity @ -40°C	mPa·s	1000
Flash Point	°C	130
Boiling point dry (min.)	°C	265
Boiling point wet (min.)	°C	170

Available packaging

30 L drum	200 L drum
-----------	------------

Specifications

FMVSS 116 DOT 3, DOT 4
ISO 4925 Class 3, Class 4
JIS K2233 Class 3, Class 4
SAE J1703, J1704
VW TL 766-X