



Power Steering Fluid | Power steering fluid

Property

- guaranteed frictionless and secure control
- lubricates and protects seals, hoses and metal components

Application area

- suitable for hydraulic systems such as power steering systems, rear axle steering systems, level control systems, hydropneumatic suspension systems, shock absorbers, stability and traction systems (ABS/ASR/ASC), electrohydraulic convertible tops, central locking, etc.
- excellent operating temperature range from -40°C to +130°C
- can be used where a Pentosin/Titan CHF 11S or CHF 202 is recommended

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Color	-	dark green
Viscosity @ 40°C	cSt	19
Viscosity @ 100°C	cSt	6
Viscosity index	-	320
Density @ 15°C	kg/l	0.83
Pour Point	°C	-55
Flash Point	°C	154

Available packaging

1 L bottle	Case 12 x 1 L bottles
------------	-----------------------

Specifications

BMW
Chrysler MS 11655
DIN 51524-2 HLP*
DIN 51524-3 HVLP
Ford M2C204-A
GM
Hyundai
ISO 7308
KIA PSF-4
MAN M 3289
MB 345.0
Opel
Porsche
Saab
Volvo 1161529
VW TL 52146
ZF TE-ML 02K

* Additional Specifications