



Hypro LV | Brake fluid DOT 4 «low viscosity»

Property

- excellent thermal stability
- easy system control thanks to low viscosity
- ensures swelling of natural, styrene-butadiene and EPDM rubbers according to specifications
- excellent corrosion protection for metal parts, even if the brake fluid is mixed with water
- optimum braking performance, even at low sub-zero temperatures
- miscible with other brake fluids with DOT 3 or DOT 4 specifications

Application area

- ideal brake fluid for modern vehicles with ASR, ESP/DSC and ABS

Note

- Attacks paint/varnish. Even an effective brake fluid can absorb water during continual use.
- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Color	-	yellow
Viscosity @ 100°C	cSt	1.5
Density @ 15°C	kg/l	1.05
Viscosity @ -40°C	mPa·s	700
Flash Point	°C	133
Boiling point dry (min.)	°C	265
Boiling point wet (min.)	°C	175

Available packaging

375 mL bottle	Case 12 x 375 mL bottles
30 L drum	

Specifications

BMW QV 34 001
FMVSS 116 DOT 3, DOT 4
ISO 4925 Class 3, Class 4, Class 6
JIS K2233 Class 3, Class 4, Class 6
SAE J1703, J1704
VW 501 14
VW TL 766-Z